



CRITICAL RENTAL
SOLUTIONS

POSITIVE DISPLACEMENT ROTARY LOBE BLOWER LINE OVERVIEW



GENERAL INFORMATION

TYPE	Rotary Lobe
FLOW RANGE	20 - 8,000 CFM
PRESSURE RANGE	15" Hg VAC - 20 PSIG
MAX TEMPRISE	280F
MIN/MAX AMBIENT	-10/120F
DRIVE MOTOR RANGE	5 - 400HP
MOTOR STARTER	DOL, Softstart, VFD
VOLTAGE	480
ELECTRICAL RATING	NEMA 4 & Hazardous
PROCESS MEDIUM	Air & Process Gas



Our fleet of heavy duty industrial bi-lobe rotary blower packages designed for reliability and adaptability for almost any installation. The open frame skid design offers a compact and sturdy design engineered for continuous duty. Our line of rotary blowers are self-contained, air-cooled, electric motor driven and rated operation in the most demanding of environments. Our rentalized packages include the following key enhancements:

Features

- Heavy Duty Open Frame Skid with Fork Pockets & Lift Points
- Outdoor Modified
- Belt Driven with OSHA Approved Belt Guard
- Inverter Duty rated premium efficiency TEFC drive motors
- Mounted & Wired NEMA 3R Disconnect/Service Breakers
- Integral Reduced Voltage Star-Delta Motor Starter
- Option for VFD Control
- Option for Hazardous Duty Service
- Option for Inlet Filter/Silencers, Relief Valves, Discharge Silencers, Additional Coolers Air & Process Gas Models Available